## NSN 4820-00-289-2135

Safety Relief Valve - Page 1 of 2

**Thread Direction:** 



View Online at https://aerobasegroup.com/nsn/4820-00-289-2135

Tilleau Direction.
Right-hand 2nd end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes 1st end
Connection Type:
Threaded internal pipe 2nd end
Adjustable Pressure Range:
+21.0/+30.0 pounds per square inch
Maximum Operating Pressure:
100.0 pounds per square inch single response
Thread Size:
1.500 inches 2nd end
Outside Diameter:
4.500 inches 1st end
Thickness:
0.438 inches 1st end
First Connection Face To Centerline Distance:
3.406 inches
Bolt Hole Diameter:
0.562 inches 1st end
Second Connection Face To Centerline Distance:
2.125 inches
Bolt Circle Diameter:
3.375 inches 1st end
Flange Face Design:
Plain 1st end
Material:
Stainless steel stem
Media For Which Designed:
Air 1st response

## NSN 4820-00-289-2135

Safety Relief Valve - Page 2 of 2



Style	Design	nator:

Angle flanged ends

**Thread Series Designator:** 

Npt 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0