NSN 4820-00-289-2245

Stop-check Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-289-2245

| Bonnet Type: | | |
|--|-------------------------|---------------------------------|
| Outside screw-yoke | | |
| Bonnet Attachment Method: | | |
| Bolted | | |
| Bolt Hole Quantity: | | |
| 6 1st end | | |
| Valve Operation Method: | | |
| Manual | | |
| Flange Shape: | | |
| Round with holes 1st end | | |
| Connection Type: | | |
| Flange 1st end | | |
| Mounting Position: | | |
| Horizontal | | |
| Features Provided: | | |
| Bonnet packing | | |
| Valve Size: | | |
| 2.500 inches | | |
| Outside Diameter: | | |
| 6.125 inches 1st end | | |
| Thickness: | | |
| 0.500 inches 1st end | | |
| First Connection Face To Centerline Distance: | | |
| 4.500 inches | | |
| Bolt Hole Diameter: | | |
| 0.562 inches 1st end | | |
| Second Connection Face To Centerline Distance: | | |
| 4.500 inches | | |
| Bolt Circle Diameter: | | |
| 5.000 inches 1st end | | |
| Flange Face Design: | | |
| Plain 1st end | | |
| Special Features: | | |
| Valve size 2.500 in. | | |
| Material: | | |
| Nickel alloy flow control device | | |
| Style Designator: | | |
| Angle flanged ends | | |
| Test Data Document: | | |
| 80064-5000s4824-1385541 drawing (this is the basic governing drawing, such a | s a contractor drawing, | original equipment manufacturer |

drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

NSN 4820-00-289-2245

Stop-check Valve - Page 2 of 2



| _ | | | | | |
|---|-----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | 116 | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0