NSN 4820-00-289-2248

Stop-check Valve - Page 1 of 2

Flow Control Device:

Angle flanged ends



View Online at https://aerobasegroup.com/nsn/4820-00-289-2248

Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
10 1st end
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal or vertical
Valve Size:
5.000 inches
Maximum Operating Pressure:
100.0 pounds per square inch single response
Outside Diameter:
9.062 inches 1st end
Thickness:
0.562 inches 1st end
First Connection Face To Centerline Distance:
7.125 inches
Bolt Hole Diameter:
0.688 inches 1st end
Second Connection Face To Centerline Distance:
7.125 inches
Bolt Circle Diameter:
7.812 inches 1st end
Flange Face Design:
Plain 1st end
Media For Which Designed:
Water-oil-gas single response
Style Designator:

NSN 4820-00-289-2248

Stop-check Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0