## NSN 4820-00-289-2248

Stop-check Valve - Page 1 of 2

Flow Control Device:

Angle flanged ends



View Online at https://aerobasegroup.com/nsn/4820-00-289-2248

| Disk   |
|--|
| Bonnet Type:                                   |
| Outside screw-yoke                             |
| Bonnet Attachment Method:                      |
| Bolted   |
| Renewable Seat Ring Type:                      |
| Threaded                                       |
| Bolt Hole Quantity:                            |
| 10 1st end                                     |
| Maximum Operating Temp:                        |
| 425.0 degrees fahrenheit single response       |
| Valve Operation Method:                        |
| Manual   |
| Flange Shape:                                  |
| Round with holes 1st end                       |
| Connection Type:                               |
| Flange 1st end                                 |
| Mounting Position:                             |
| Horizontal or vertical                         |
| Valve Size:                                    |
| 5.000 inches                                   |
| Maximum Operating Pressure:                    |
| 100.0 pounds per square inch single response   |
| Outside Diameter:                              |
| 9.062 inches 1st end                           |
| Thickness:                                     |
| 0.562 inches 1st end                           |
| First Connection Face To Centerline Distance:  |
| 7.125 inches                                   |
| Bolt Hole Diameter:                            |
| 0.688 inches 1st end                           |
| Second Connection Face To Centerline Distance: |
| 7.125 inches                                   |
| Bolt Circle Diameter:                          |
| 7.812 inches 1st end                           |
| Flange Face Design:                            |
| Plain 1st end                                  |
| Media For Which Designed:                      |
| Water-oil-gas single response                  |
| Style Designator:                              |

## NSN 4820-00-289-2248

Stop-check Valve - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A530b0