NSN 4820-00-289-3769

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-3769

Pipe Size Accommodated:
1.500 inches 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
6 2nd end
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Connection Style:
Swivel nut, gasket sea (tube) all ends
Valve Operation Method:
Air
Flange Shape:
Round with holes 2nd end
Connection Type:
Unthreaded internal pipe 1st end
Adjustable Pressure Range:
+31.0/+48.0 pounds per square inch
Maximum Operating Pressure:
100.0 pounds per square inch single response
Outside Diameter:
5.062 inches 2nd end
Thickness:
0.562 inches 2nd end
Bolt Hole Diameter:
0.562 inches 2nd end
Bolt Circle Diameter:
3.938 inches 2nd end
Flange Face Design:
Plain 2nd end
Special Features:
W/lifting lever
Material:
Nickel alloy flow control device
Media For Which Designed:
Steam single response
Style Designator:
Angle

NSN 4820-00-289-3769

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0