NSN 4820-00-289-3780

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk Loading Method:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-289-3780

Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Pressure tight outlet side
Valve Size:
1.000 inches
Adjustable Pressure Range:
+18.0/+32.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch 2nd response
Outside Diameter:
4.250 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
4.625 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
3.500 inches
Bolt Circle Diameter:
3.125 inches all ends
Flange Face Design:
Plain all ends
Special Features:
W/lifting lever
Material:
Stainless steel stem
Media For Which Designed:
Fuel/oil, hydrocarbon 1st response

NSN 4820-00-289-3780

Safety Relief Valve - Page 2 of 2



•		
StVID	l Jacian	ator.
OLYIC	Design	atoi.

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0