NSN 4820-00-289-3797

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-3797

Pipe Size Accommodated:
0.375 inches 1st end
Thread Direction:
Right-hand all ends
Flow Control Device:
Piston
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+15.0/+100.0 pounds per square inch
Maximum Operating Pressure:
500.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Material:
Steel seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-289-3797

Safety Relief Valve - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A046b0