NSN 4820-00-289-3806

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-3806

Pipe Size Accommodated:
2.000 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
11-1/2 2nd end
Adjustable Pressure Range:
+121.0/+250.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
2.000 inches 1st end
Material:
Steel stem
Material Specification:
Qq-c-390, alloyb5/d/ federal specification single material response body
Media For Which Designed:
Steam single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

NSN 4820-00-289-3806

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0