NSN 4820-00-289-3818

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-3818

| Thread Direction: |
|--|
| Right-hand 2nd end |
| Disk Loading Method: |
| Spring |
| Bolt Hole Quantity: |
| 4 1st end |
| Maximum Operating Temp: |
| 425.0 degrees fahrenheit single response |
| Connection Style: |
| Plain, optional en (pipe) 2nd end |
| Flange Shape: |
| Round with holes 1st end |
| Connection Type: |
| Threaded internal pipe 2nd end |
| Adjustable Pressure Range: |
| +4.0/+9.0 pounds per square inch |
| Maximum Operating Pressure: |
| 100.0 pounds per square inch single response |
| Thread Size: |
| 1.000 inches 2nd end |
| Outside Diameter: |
| 4.250 inches 1st end |
| Bolt Hole Diameter: |
| 0.562 inches 1st end |
| Bolt Circle Diameter: |
| 3.125 inches 1st end |
| Flange Face Design: |
| Plain 1st end |
| Special Features: |
| W/lifting lever |
| Material: |
| Nickel alloy seat |
| Media For Which Designed: |
| Steam single response |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Npt 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

-

NSN 4820-00-289-3818

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0