NSN 4820-00-289-3820

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-289-3820

0.500 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
14 2nd end
Adjustable Pressure Range:
+0.0/+12.0 pounds per square inch
Maximum Operating Pressure:
500.0 pounds per square inch single response
Thread Size:
0.500 inches 2nd end
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-289-3820

Safety Relief Valve - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A046b0