

View Online at <https://aerobasegroup.com/nsn/4820-00-289-3833>

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Welded

Bolt Hole Quantity:

3 all ends

Maximum Operating Temp:

425.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Pressure tight outlet side

Adjustable Pressure Range:

+28.0/+45.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

3.562 inches all ends

Thickness:

0.375 inches all ends

First Connection Face To Centerline Distance:

3.000 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

3.250 inches

Bolt Circle Diameter:

2.438 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

1.375 inches all ends

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0