NSN 4820-00-289-3833

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-3833

| Flow Control Device: |
|--|
| Disk |
| Bonnet Type: |
| Exposed spring |
| Bonnet Attachment Method: |
| Bolted |
| Disk Loading Method: |
| Spring |
| Renewable Seat Ring Type: |
| Welded |
| Bolt Hole Quantity: |
| 3 all ends |
| Maximum Operating Temp: |
| 425.0 degrees fahrenheit single response |
| Valve Operation Method: |
| Automatic or manual |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Features Provided: |
| Pressure tight outlet side |
| Adjustable Pressure Range: |
| +28.0/+45.0 pounds per square inch |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter: |
| 3.562 inches all ends |
| Thickness: |
| 0.375 inches all ends |
| First Connection Face To Centerline Distance: |
| 3.000 inches |
| Bolt Hole Diameter: |
| 0.562 inches all ends |
| Second Connection Face To Centerline Distance: |
| 3.250 inches |
| Bolt Circle Diameter: |
| 2.438 inches all ends |
| Flange Face Design: |
| Raised straight all ends |
| Raised Face Height: |
| 0.062 inches all ends |

NSN 4820-00-289-3833

Safety Relief Valve - Page 2 of 2



1.375 inches all ends

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0