NSN 4820-00-289-3871

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Exposed spring

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-289-3871

Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Adjustable Pressure Range:
+31.0/+60.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
4.500 inches 1st end
Thickness:
0.500 inches 1st end
First Connection Face To Centerline Distance:
4.375 inches
Bolt Hole Diameter:
0.562 inches 1st end
Second Connection Face To Centerline Distance:
4.375 inches
Bolt Circle Diameter:
3.375 inches 1st end
Flange Face Design:
Plain 1st end
Material:
Stainless steel stem
Media For Which Designed:
Steam single response
Style Designator:
Angle flanged ends

NSN 4820-00-289-3871

Safety Relief Valve - Page 2 of 2



c	pecif	icati	on	Or	C+2	nd	ard	ı
3	becn	icati	on '	Ul I	ota	na	arc	1.

1 type and d composition

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0