# NSN 4820-00-289-4141

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-4141

Thread Class:

3b all ends

**Thread Direction:** 

Right-hand all ends

## Offset Distance:

1.750 inches

### Flow Control Device:

Disk

#### Disk Loading Method:

Spring

### Valve Discharge Flow Rate:

2552.4 pounds per hour

#### **Maximum Operating Temp:**

160.0 degrees fahrenheit single response

#### **Connection Style:**

Gasket sea (boss) all ends

# Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded internal boss all ends

#### Mounting Facility:

Threaded fastener

#### Adjustable Pressure Range:

+2300.0/+3850.0 pounds per square inch

#### Maximum Operating Pressure:

3850.0 pounds per square inch single response

#### Thread Size:

0.750 inches all ends

#### Material:

Aluminum alloy

#### Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

#### Style Designator:

Tee w/offset

#### **Thread Series Designator:**

Unf all ends

#### Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

# NSN 4820-00-289-4141

Safety Relief Valve - Page 2 of 2

**Fiig:** A046b0

