NSN 4820-00-289-4346

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-289-4346

DISK
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Adjustable Pressure Range:
+18.0/+32.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
4.250 inches 1st end
Thickness:
0.500 inches 1st end
First Connection Face To Centerline Distance:
3.562 inches
Bolt Hole Diameter:
0.562 inches 1st end
Second Connection Face To Centerline Distance:
4.688 inches
Bolt Circle Diameter:
3.125 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
2.000 inches 1st end
Material:
Stainless steel stem

NSN 4820-00-289-4346

Safety Relief Valve - Page 2 of 2



Steam single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0