NSN 4820-00-289-4359

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-289-4359

view Offilite at https://aerobasegroup.com/hist//4020
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
51500.0 pounds per hour
Bolt Hole Quantity:
8 2nd end
Maximum Operating Temp:
330.0 degrees fahrenheit single response
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Adjustable Pressure Range:
+21.0/+27.0 pounds per square inch
Maximum Operating Pressure:
33.0 pounds per square inch single response
Outside Diameter:
15.000 inches 1st end
Bolt Hole Diameter:
0.812 inches 1st end
Bolt Circle Diameter:
11.750 inches 2nd end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.625 inches 2nd end
Raised Face Diameter:
10.625 inches 2nd end
Special Features:
W/lifting lever
Material:
Stainless steel stem
Style Designator:
Angle
Furnished Items And Quantity:
1 sight gage
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-00-289-4359

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0