NSN 4820-00-291-6670

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-291-6670

Pipe Size Accommodated:
3.000 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
297.0 gallons per minute
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
8 2nd end
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
3.000 inches 2nd end
Opening Pressure Setting:
85.0 pounds per square inch
Material:
Copper alloy body
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-291-6670

Safety Relief Valve - Page 2 of 2



Demi			

No

Fiig:

A046b0