NSN 4820-00-291-6670

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-291-6670

Pipe Size Accommodated:

3.000 inches 2nd end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

297.0 gallons per minute

Maximum Operating Temp:

406.0 degrees fahrenheit single response

Connection Style:

Plain (pipe) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

8 2nd end

Maximum Operating Pressure:

150.0 pounds per square inch single response

Thread Size:

3.000 inches 2nd end

Opening Pressure Setting:

85.0 pounds per square inch

Material:

Copper alloy body

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4820-00-291-6670

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

