NSN 4820-00-292-2243

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-292-2243

| Thread Class: |
|---|
| 2a all ends |
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Stem or disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Integral |
| Maximum Operating Temp: |
| 300.0 degrees fahrenheit single response |
| Connection Style: |
| Flareless (tube) all ends |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Threaded external tube all ends |
| Mounting Facility: |
| Panel |
| Features Provided: |
| Bonnet packing |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.562 inches all ends |
| Seat Angle: |
| 20.0 degrees all ends |
| Material: |
| Steel comp 316 seat |
| Material Specification: |
| 66 federal standard single material response body |
| Media For Which Designed: |
| Water-oil-gas single response |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Unf all ends |
| Furnished Items And Quantity: |
| 3 nut and 4 ferrule |
| Shelf Life: |
| N/a |

N/a

NSN 4820-00-292-2243

Globe Valve - Page 2 of 2



| Demilitarization: | |
|-------------------|--|
| No | |
| Fiig: | |
| A046b0 | |

Mil-std (military Standard):

Unit Of Measure:

spec.