NSN 4820-00-293-7687

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-293-7687 **Thread Direction:** Right-hand all ends **Flow Control Device:** Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Union **Maximum Operating Temp:** 550.0 degrees fahrenheit 1st response150.0 degrees fahrenheit 2nd response **Connection Style:** Plain, optional en (pipe) all ends **Valve Operation Method:** Manual **Connection Type:** Threaded internal pipe all ends **Features Provided:** Bonnet packing **Maximum Operating Pressure:** 200.0 pounds per square inch 1st response400.0 pounds per square inch 2nd response **Thread Size:** 0.500 inches all ends Material: Copper alloy 922 bodycopper alloy flow control devicecopper alloy 922 seatcopper alloy stem **Material Specification:** Qq-c-390, alloy d4 federal specification single material response bodyqq-c-390, alloy d4 federal specification single material response seat Media For Which Designed: Steam 1st responsewater-oil-gas 2nd response Style Designator: Straight thru **Thread Series Designator:** Npt all ends **Specification Or Standard:** 1 type and c class Shelf Life: N/a **Unit Of Measure:**

No Fiig:

Demilitarization:

A046b0