NSN 4820-00-294-2683

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-294-2683

Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
300.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
14 2nd end
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
Opening Pressure Setting:
100.0 pounds per square inch
Material:
Steel stem
Material Specification:
Qq-c-390, alloyd4/d/ federal specification single material response seat
Media For Which Designed:
Water-oil-gas 2nd response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Specification Or Standard:

1 type and a style and 2 class and 0.750 size

NSN 4820-00-294-2683

Safety Relief Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0