## NSN 4820-00-295-6963

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-295-6963

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
-40.0 degrees fahrenheit 1st response250.0 degrees fahrenheit 2nd response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Adjustable Pressure Range:
+29.0/+72.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
28.3 pounds per square inch
Material:
Steel comp 303
Material Specification:
Qq-s-764, type303-canceled federal specification single material response
Media For Which Designed:
Helium 3rd response
Style Designator:
"y" angle
Thread Series Designator:
Npt 1st end
Furnished Items And Quantity:
1 deflector cap
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 4820-00-295-6963

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0