NSN 4820-00-295-6963

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-295-6963

Pipe Size Accommodated:

0.250 inches 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

-40.0 degrees fahrenheit 1st response250.0 degrees fahrenheit 2nd response

Connection Style:

Plain (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external pipe 1st end

Adjustable Pressure Range:

+29.0/+72.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.250 inches 1st end

Opening Pressure Setting:

28.3 pounds per square inch

Material:

Steel comp 303

Material Specification:

Qq-s-764, type303-canceled federal specification single material response

Media For Which Designed:

Helium 3rd response

Style Designator:

"y" angle

Thread Series Designator:

Npt 1st end

Furnished Items And Quantity:

1 deflector cap

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4820-00-295-6963

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

