NSN 4820-00-295-8614

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-295-8614

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end Flow Control Device:
Poppet Disk Loading Methods
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Flared (tube) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
4000.0 pounds per square inch single response
Thread Size:
0.437 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Outside Diameter Tube Accommodated:
0.312 inches 2nd end
Material:
Steel flow control device
Material Specification:
Qq-s-764, type 440 federal specification single material response flow control device
Media For Which Designed:
Air single response
Style Designator:
Straight thru
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-295-8614

Check Valve - Page 2 of 2



em			

No

Fiig:

A530b0