

| NSN 4820-00-296-9985 Safety Relief Valve - Page 1 of 1 |
|---|
| View Online at https://aerobasegroup.com/nsn/4820-00-296-9985 |
| Pipe Size Accommodated: |
| 0.125 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 200.0 degrees celsius single response |
| Connection Style: |
| Plain (pipe) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external pipe 1st end |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch single response |
| Thread Size: |
| 0.125 inches 1st end |
| Opening Pressure Setting: |
| 27.0 pounds per square inch |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Qq-s-764, type303-canceled federal specification single material response |
| Media For Which Designed: |
| Oxygen, gaseous 5th response |
| Style Designator: |
| Straight through w/baffle |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0