NSN 4820-00-297-0004

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-297-0004

0.125 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Minimum Operating Temp:
-100.0 degrees fahrenheit
Connection Style:
G46b plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.125 inches 1st end
Opening Pressure Setting:
125.0 pounds per square inch
Material:
Steel comp 303
Material Specification:
66 federal standard single material response
Media For Which Designed:
Nitrogen, gaseous single response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Furnished Items And Quantity:
1 deflector cap
Chalf I ifa.
Shelf Life:

NSN 4820-00-297-0004

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0