NSN 4820-00-300-2528

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-300-2528

| Body Material: |
|---|
| Steel |
| Body Style: |
| Straight thru |
| Media For Which Designed: |
| Water |
| First End Connection Type: |
| Plain face flange |
| First End Style Designator: |
| Plain |
| First End Flange Shape Style: |
| Rectangular (includes square) w/ bolt holes |
| First End Flange Thickness: |
| 3.216 inches |
| First End Flange Length: |
| 5.910 inches |
| First End Flange Width: |
| 5.860 inches |
| First End Bolt Hole Quantity: |
| 4 |
| First End Bolt Hole Diameter: |
| 0.750 inches |
| Second End Relationship With First End: |
| Identical |
| Flow Control Device: |
| Disk, circular |
| Flow Control Device Material: |
| Brass |
| End Connection Quantity: |
| 2 |
| Valve Discharge Flow Rate: |
| 300.0 gallons per minute |
| Regulation Type: |
| Automatic single stage |
| First End Center To Center Distance Between Holes Along Length: |
| 4.280 inches |
| First End Center To Center Distance Between Holes Along Width: |
| 4.280 inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 4820-00-300-2528

Calibrated Flow Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A21100

