

View Online at <https://aerobasegroup.com/nsn/4820-00-300-6914>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Width:

5.625 inches all ends

Length:

5.625 inches all ends

Valve Operation Method:

Manual

Flange Shape:

Rectangular with holes all ends

Connection Type:

Flange all ends

Mounting Facility:

Lug

Features Provided:

Valve stem lock shield and bonnet packing

Valve Size:

2.500 inches

Maximum Operating Pressure:

400.0 pounds per square inch single response

Face To Face Distance:

9.250 inches

Thickness:

1.500 inches all ends

First Connection Face To Centerline Distance:

5.000 inches

Bolt Hole Diameter:

0.875 inches all ends

Second Connection Face To Centerline Distance:

5.000 inches

Center To Center Distance Between Bolt Holes Along Length:

5.000 inches all ends

Center To Center Distance Between Bolt Holes Along Width:

4.000 inches all ends

Flange Face Design:

Raised with curve and radius 1st end

Raised Face Height:

0.156 inches 1st end

Raised Face Diameter:

0.750 inches 1st end

Recess Diameter:

2.969 inches 2nd end

Recess Depth:

3.750 inches 2nd end

Material:

Steel stem

Media For Which Designed:

Ammonia, liquid single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0