## NSN 4820-00-302-6352

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-302-6352

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand all ends
Flow Control Device:
Needle
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Mounting Facility:
Bulkhead
Features Provided:
Bonnet packing
Adjustable Pressure Range:
+1000.0/+3000.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.250 inches all ends
Material:
Stainless steel flow control device
Media For Which Designed:
Oil, hydraulic 2nd response
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-302-6352

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0