# NSN 4820-00-302-6352

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-302-6352

Pipe Size Accommodated:

0.250 inches 1st end

**Thread Direction:** 

Right-hand all ends

# Flow Control Device:

Needle

#### Bonnet Type:

Inside spring

### **Bonnet Attachment Method:**

Integral

**Disk Loading Method:** 

Spring

#### Maximum Operating Temp:

180.0 degrees fahrenheit single response

#### **Connection Style:**

Plain, optional en (pipe) all ends

# Valve Operation Method:

Automatic

## **Connection Type:**

Threaded internal pipe all ends

# Mounting Facility:

Bulkhead

#### Features Provided:

Bonnet packing

## Adjustable Pressure Range:

+1000.0/+3000.0 pounds per square inch

## Maximum Operating Pressure:

3000.0 pounds per square inch single response

## **Thread Size:**

0.250 inches all ends

#### Material:

Stainless steel flow control device

# Media For Which Designed:

Oil, hydraulic 2nd response

# Style Designator:

Angle

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 4820-00-302-6352

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

