## NSN 4820-00-303-5464

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-303-5464

Body Material:
Aluminum alloy
Body Style:
Tee
Stem Material:
Aluminum alloy
Furnished Items:
Restrictor, flow
Media For Which Designed:
Hydraulic oil
First End Connection Type:
Threaded internal boss
First End Style Designator:
Gasket seal
First End Thread Size And Series/type Designator:
3/4-16 unf
First End Thread Class:
2b
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Identical
Third End Relationship With Preceding Ends:
Identical with first end
Seat Material:
Aluminum alloy
Flow Control Device:
Needle
Flow Control Device Material:
Aluminum alloy
End Connection Quantity:
3
Valve Discharge Flow Rate:
8.0 gallons per minute
Mounting Facility:
Panel
Regulation Type:
Manual single stage
Manual Control Method:
Screw
Maximum Inlet Pressure Rating:
1710.0 pounds per square inch

## NSN 4820-00-303-5464

Calibrated Flow Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A21100

