## ľ



304-6705 V

<b>NSN 4820-00-304-6705</b> Safety Relief Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-00-30
Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
140.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
1800.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
1800.0 pounds per square inch
Special Features:
End color coded red to indicate pressure
Material:
Aluminum alloy seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

---

No

Demilitarization:

## NSN 4820-00-304-6705

Safety Relief Valve - Page 2 of 2

**Fiig:** A046b0

