NSN 4820-00-311-5041

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-311-5041

View Online at https://aerobasegroup.com/nsn/4820-00-311-5041
Pipe Size Accommodated:
0.375 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
18 1st end
Adjustable Pressure Range:
+40.0/+125.0 pounds per square inch
Maximum Operating Pressure:
125.0 pounds per square inch single response
Thread Size:
0.375 inches 1st end
Opening Pressure Setting:
90.0 pounds per square inch
Special Features:
The end connection identified above as the second end is the valve inlet
Material:
Steel comp 303 flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:

Angle

NSN 4820-00-311-5041

Safety Relief Valve - Page 2 of 2



Thread Series Designator:
Npt 1st end
Furnished Items And Quantity:
1 cap
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0