## NSN 4820-00-321-0909



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-321-0909 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 135.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 16 all ends **Maximum Operating Pressure:** 35.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends Seat Angle: 37.0 degrees all ends **Opening Pressure Setting:** 18.0 pounds per square inch Material: Aluminum alloy 2024 body **Material Specification:** Qq-a-225/6 federal specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon 2nd response **Surface Treatment:** Anodize **Style Designator:** Straight thru **Thread Series Designator:** 

Unj all ends Shelf Life:

N/a

## NSN 4820-00-321-0909

Check Valve - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A530b0