

View Online at https://aerobasegroup.com/nsn/4820-00-328-8202

| view Online at https://aerobasegroup.com/nsn/4820-00-328-8202 |
|---|
| Body Material: |
| Aluminum alloy |
| Outside Surface Treatment: |
| Anodized |
| Media For Which Designed: |
| Air |
| First End Connection Type: |
| Threaded external tube |
| First End Style Designator: |
| Flared |
| First End Outside Diameter Tube Accommodated: |
| 0.250 inches |
| First End Thread Size And Series/type Designator: |
| 7/16-20 unf |
| First End Thread Class: |
| 3a |
| First End Thread Direction: |
| Right-hand |
| Second End Relationship With First End: |
| Not identical |
| Second End Connection Type: |
| Threaded internal boss |
| Second End Style Designator: |
| Gasket seal |
| Second End Thread Size And Series/type Designator: |
| 7/16-20 unf |
| Second End Thread Class: |
| 3b |
| Second End Thread Direction: |
| Right-hand |
| Third End Relationship With Preceding Ends: |
| Identical with second end |
| Seat Material: |
| Aluminum alloy |
| First End Seat Angle In Deg: |
| 37.0 |
| Flow Control Device: |
| Poppet |
| Flow Control Device Material: |
| Aluminum alloy |
| End Connection Quantity: |
| 0 |



Outlet Pressure Range:

+0.0/+10.0 pounds per square inch

Regulation Type:

Automatic double stage

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

10.0 pounds per square inch

Filter:

Not included

Tempurature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A21100