NSN 4820-00-331-3537

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-331-3537

| Pipe Size Accommodated: |
|--|
| 0.250 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 250.0 degrees fahrenheit single response |
| Connection Style: |
| Plain, optional en (pipe) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal pipe 1st end |
| Thready Qty Per Inch (tpi): |
| 18 1st end |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch single response |
| Thread Size: |
| 0.250 inches 2nd end |
| Opening Pressure Setting: |
| 20.0 pounds per square inch |
| Material: |
| Stainless steel flow control device |
| Media For Which Designed: |
| Nitrogen, gaseous 3rd response |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |