NSN 4820-00-332-8426



Lift-check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-332-8426 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Gasket seal (boss) 1st end **Valve Operation Method:** Manual **Connection Type:** Threaded internal boss 1st end **Mounting Position:** Horizontal or vertical **Features Provided:** Bonnet packing Thready Qty Per Inch (tpi): 16 1st end **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Special Features:** Handle turns 90.0 degrees cw for open position Material: Steel stem Media For Which Designed: Oil, hydraulic single response **Surface Treatment:** Anodize **Style Designator:**

Thread Series Designator: Unf 1st end

Straight thru

NSN 4820-00-332-8426

Lift-check Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0