

View Online at <https://aerobasegroup.com/nsn/4820-00-340-1405>

End Application:

Qtruck, utilities, tow carrier-w/sa, 1 1/4 ton, w/winch, hmwv; truck, ambulance, 2-litter, soft top, 1 1/4 ton hmwv; truck, vehicle system, 1 1/4-ton (hmwv); truck, utility, cargo troop carrier, 5/4-ton w/e (m998)

Product Name:

Bleeder valve

Special Features:

Steel, spec data, sae, 1112; zinc-plated finish; dim. Data, 1.17 in. Lg o/a, 0.38 in. Across hex flats, 0.10 in. Lg hex, 0.78 in. From valve end to nearest hex shoulder; barbed type hose connector, barber type data, 0.17 in. From hex shoulder to nearest edge of barber hose connector, 0.313 in. Max, 0.303 in. Min, largest diameter of hose connector, 0.203 in. Max, 0.187 in. Min, smallest diameter of hose connector, 0.290 in. Lg hose connector; valve seat end data, 0.277 in. Largest od of taper, 3/32 in. Lg taper, 0.280 in. Lg excl thd portion, 0.210 in. From center of inlet hole to valve end, 3/32 in. Diameter inlet hole, external thd data, 3/8 in. - 24 thd, nf, rh, class 2 fit, 0.45 in. Lg; drain hole data, 1/8 in. Dia, 1 in. Lg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0