NSN 4820-00-341-2987

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-341-2987 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring Valve Discharge Flow Rate: 115.0 pounds per hour **Maximum Operating Temp:** 160.0 degrees fahrenheit 2nd response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Valve stem lock shield and bonnet packing and pressure tight outlet side **Adjustable Pressure Range:** +2100.0/+4100.0 pounds per square inch **Maximum Operating Pressure:** 4100.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends **Outside Diameter Tube Accommodated:** 0.625 inches all ends Material: Steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Angle **Thread Series Designator:** Unf all ends

Shelf Life:

N/a

NSN 4820-00-341-2987

Safety Relief Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0