NSN 4820-00-341-3906

Check Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-341-3906

Disk
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
450.0 degrees fahrenheit 2nd response
Connection Style:
Beaded (hose) 2nd end
Width:
1.820 inches 1st end
Length:
1.830 inches 1st end
Valve Operation Method:
Automatic
Flange Shape:
Rectangular with holes 1st end
Connection Type:
Unthreaded external hose 2nd end
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
36.0 pounds per square inch single response
Thickness:
0.255 inches 1st end
Bolt Hole Diameter:
0.220 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
1.325 inches 1st end
Center To Center Distance Between Bolt Holes Along Width:
1.325 inches 1st end
Flange Face Design:
Recessed straight 1st end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, alloy 2024, t851 federal specification single material response
Media For Which Designed:
Air single response
Surface Treatment:
Anodize

NSN 4820-00-341-3906

Check Valve - Page 2 of 2



Surface Treatment Speci

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Straight thru

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.