

View Online at <https://aerobasegroup.com/nsn/4820-00-345-4698>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Stem or disk

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

2.0 cubic feet per minute

**Connection Style:**

Flared (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Thready Qty Per Inch (tpi):**

20 1st end

**Adjustable Pressure Range:**

+32.0/+35.0 pounds per square inch

**Maximum Operating Pressure:**

35.0 pounds per square inch single response

**Thread Size:**

0.437 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Opening Pressure Setting:**

33.5 pounds per square inch

**Outside Diameter Tube Accommodated:**

0.250 inches 1st end

**Material:**

Aluminum alloy stem and rubber chloroprene class cr stem

**Media For Which Designed:**

Air single response

**Surface Treatment:**

Anodize

**Style Designator:**

Straight through w/baffle

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A046b0