NSN 4820-00-346-2536

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-346-2536

| view Online at https://aerobasegroup.com/nsn/4820-00-346-2536 |
|---|
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Poppet |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Integral |
| Maximum Operating Temp: |
| 500.0 degrees fahrenheit single response |
| Connection Style: |
| Plain, optional en (pipe) 2nd end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal pipe 2nd end |
| Maximum Operating Pressure: |
| 280.0 pounds per square inch single response |
| Thread Size: |
| 0.500 inches all ends |
| Opening Pressure Setting: |
| 275.0 pounds per square inch |
| Material: |
| Steel comp 303 flow control device |
| Media For Which Designed: |
| Bromochloromethane single response |
| Style Designator: |
| Straight through note: to be used for valve bodies of separable sections. |
| Thread Series Designator: |
| Npt all ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |
| |