## NSN 4820-00-348-4395

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-348-4395 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Disk Loading Method:** Spring **Connection Style:** Gasket seal (boss) 1st end **Connection Type:** Threaded internal tube 1st end **Mounting Facility:** Threaded fastener **Mounting Position:** Horizontal Thready Qty Per Inch (tpi): 18 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end Seat Angle: 45.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.375 inches 1st end **Special Features:** 0.228 in. Stem stroke for reverse flow Material: Steel flow control device Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Style Designator:** Straight through w/offset **Thread Series Designator:** Unf 1st end Shelf Life: N/a

**Demilitarization:** 

Yes - demil/mli

**Unit Of Measure:** 

## NSN 4820-00-348-4395

Lift-check Valve - Page 2 of 2



Fiig:

A530b0