## NSN 4820-00-348-8281



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-348-8281 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 450.0 degrees fahrenheit 2nd response **Connection Style:** External seat for gasket seal (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss all ends **Mounting Position:** Horizontal Thready Qty Per Inch (tpi): 20 all ends **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.719 inches 1st end **Special Features:** The end connection identified above as the second end is the valve inlet Material: Steel comp 630 body **Material Specification:** Ams 5643 assn standard single material response body Media For Which Designed: Hydraulic fluid, petroleum base single response **Surface Treatment: Passivate Surface Treatment Specification:** 

Mil-s-5002 military specification single treatment response

**Style Designator:** 

Straight thru

## **Thread Series Designator:**

Unjs all ends

## Shelf Life:

N/a

## NSN 4820-00-348-8281

Check Valve - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-s-5002 spec.