

NSN 4820-00-348-8284
Check Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-00-348-8284
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Maximum Operating Temp:
450.0 degrees fahrenheit 2nd response
Connection Style:
External seat for gasket seal (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external boss all ends
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
20 2nd end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.844 inches 1st end
Special Features:
The end connection identified above as the second end is the valve inlet
Material:
Steel comp 630 body
Material Specification:
Ams 5643 assn standard single material response body
Media For Which Designed:
Hydraulic fluid, petroleum base single response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unjs all ends
Shelf Life:

Unit Of Measure:

N/a

NSN 4820-00-348-8284

Check Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-s-5002 spec.