NSN 4820-00-353-7642

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-353-7642

Flow Control Device:
Disk
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Width:
4.010 inches 1st end
Length:
4.010 inches 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Rectangular with holes 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
120.0 pounds per square inch single response
Face To Face Distance:
3.865 inches
Thickness:
0.185 inches 2nd end
Bolt Hole Diameter:
0.265 inches 2nd end
Center To Center Distance Between Bolt Holes Along Length:
3.250 inches 2nd end
Center To Center Distance Between Bolt Holes Along Width:
3.250 inches 1st end
Flange Face Design:
Plain 2nd end
Material:
Aluminum alloy 384.0
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response
Style Designator:

Straight thru

NSN 4820-00-353-7642

Check Valve - Page 2 of 2



-			 	
•	hΔ	Iŧ.	ife:	

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.