NSN 4820-00-357-5127

Lift-check Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside spring

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-357-5127

Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Valve Size:
2.000 inches
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
4.344 inches all ends
Face To Face Distance:
3.750 inches
Thickness:
1.688 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
3.625 inches all ends
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Surface Treatment:
Paint

NSN 4820-00-357-5127

Lift-check Valve - Page 2 of 2



Sty					

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0