## NSN 4820-00-358-1008

Shuttle Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-358-1008 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Piston Valve Discharge Flow Rate: 3.4 gallons per minute **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Flareless (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Facility:** Threaded fastener **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends Seat Angle: 12.0 degrees all ends Material: Stainless steel Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8635, type 1 military specification single treatment response **Style Designator:** Cross **Thread Series Designator:** Unjf all ends Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 4820-00-358-1008

Shuttle Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8635 spec.