

View Online at <https://aerobasegroup.com/nsn/4820-00-358-1993>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

16 1st end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Mounting Position:

Horizontal

Features Provided:

Bonnet packing

Valve Size:

12.000 inches

Maximum Operating Pressure:

50.0 pounds per square inch single response

Outside Diameter:

16.562 inches 1st end

Thickness:

0.688 inches 1st end

First Connection Face To Centerline Distance:

13.375 inches

Bolt Hole Diameter:

0.812 inches 1st end

Second Connection Face To Centerline Distance:

13.375 inches

Bolt Circle Diameter:

15.000 inches 1st end

Flange Face Design:

Plain 1st end

Special Features:

Right hand lever assembly

Material:

Nickel alloy flow control device

Media For Which Designed:

Water, salt single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0