

View Online at <https://aerobasegroup.com/nsn/4820-00-369-7777>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Needle

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Integral

Maximum Operating Temp:

70.0 degrees fahrenheit single response

Connection Style:

Inverted flare (tube) 1st end

Valve Operation Method:

Manual

Connection Type:

Threaded external tube 2nd end

Mounting Facility:

Bulkhead

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

18 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Seat Angle:

20.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Material:

Steel comp 416se flow control device

Material Specification:

Aisi 416e/sae 51416 se assn standard single material response flow control device

Media For Which Designed:

Air single response

Surface Treatment:

Nickel

Style Designator:

Straight thru

Thread Series Designator:

Unf 1st end

Furnished Items And Quantity:

2 nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0